10MSP MOBILE STOCK PICKER



Performance

| Platform Height | 10 ft | 3.05 m |
|--------------------------------|----------------------|--------------|
| Working Height | 16 ft | 4.88 m |
| Drive Height | Max. Platform Height | |
| Stowed Height | 57 in. | 145 cm |
| Platform Entry Height | 13.75 in. | 35 cm |
| Platform Size (W x L) | 20 x 27 in. | 49.5 x 69 cm |
| Overall Vehicle Length | | |
| Chassis Length | 61 in. | 155 cm |
| Overall Vehicle Width | | |
| Chassis Width | 32.5 in. | 83 cm |
| Chassis Width (without bumper) | 29.5 in. | 75 cm |
| Gross Vehicle Weight | 1,100 lb | 499 kg |
| Capacity | | |
| Platform | 350 lb | 159 kg |
| Carry Deck | 250 lb | 113 kg |
| Material Tray | 250 lb | 113 kg |
| Max. Drive Speed | | |
| Platform Lowered | 5.0 mph | 8.0 km/h |
| Platform Elevated | 0.5 mph | 0.8 km/h |
| Turning Radius | Zero | |
| Gradeability | 15% | |
| Underclearance | 2 in. | 5 cm |
| | | |

Standard Specifications

Power Source

| | 4 Sealed 210 amp-hr Maintenance Free (AGM) 25 Amp Automatic | |
|---|--|--|
| Drive System 4 Brus Tires | ısh Direct Electric (planetary gear) | |
| Rear Drive & Steer Wheels 12.62 > Non-Marking Front Caster Wheels 8 x 2.5 | x 4 in. 32 x 10 cm | |



Standard Features

- Heavy Duty Planetary Gear Drive Motors
- Simultaneous Lift and Drive Capability
- Point & Go® One-Hand Drive and Steer System
- Proportional Drive
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators Platform and Base
- Lubrication-Free Anodized Aluminum Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front and Rear
- Programmable Motion Alarm
- Slope Cut-Out Control Interlock

- Stand-On Foot Switch Operation Enable Control
- Platform Gate Operation Interlock
- · Adjustable Height Material Tray
- Non-Marking Tire Material
- Lanyard Attachment Anchor Point
- Hourmeter
- Horn
- Shipping Skid
- Transportation Tie Downs
- Side and Front Bumpers
- ANSI, OSHA & CSA Compliant

Accessories & Options

- Charger Cord Retractor
- Programmable 4-Digit Security Lock
- Guide Roller System
- · Remote Manual Descent
- Object Sensing Pad
- Electrically-Powered Material Tray (200lb Capacity)
- Rubber Floor Mat

The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

Part No.: 3132119 R1219_A92.20 Printed in USA



JLG Industries, Inc.

1 JLG Drive McConnellsburg, PA 17233-9533 Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT Fax 717-485-6417

www.jlg.com

An Oshkosh Corporation Company